

样板汇总

型号名称 功能	Raise_CX32 _Euro	Raise_VCTP _Euro_s	Raise_VCTP _3A_s	Raise_VCTP _Euro_L	Raise_VCTP _3A_L	Raise_HTV255 _3A	Raise_VCTP FRCH_Euro	Raise_VCTP FRCH_3A
Panel interface	LVDS	Dual LVDS	Dual LVDS	Dual LVDS	Dual LVDS	TTL	Dual LVDS	Dual LVDS
MAX. Resolution	1366*768	1440*900				800*600	60Hz : 1920*1080 , 120Hz : 1366*768	
Suggesting Size	≥32"	15"~26"		≥32"		15"~20"	≥32"	
RF input	√	√	√	√	√	√	√	√
SCART	1full /1 half	1full		1full /1 half			1full /1half	
S-VIDEO 输入			1 0	1	1	1	1	1
A/V 输入			2 1	1	2	2	1	2
YPbPr 输入	1	1	0 1	1	1	1	1	1
D-SUB(VGA)输入	1	1	1	1	1	1	1	1
HDMI 输入	2			1	1		2	2
扩展口	DVB-T、USB、侧 AV	DVB-T		DVB-T			DVB-T	2 路 USB
TELETEXT(Pages)	500	10		100			1000	
Ni cam	√	√		√			√	
Comb filter	3D	2D	2D	3D	3D	2D	3D	3D
Noise reduction	√			√	√	√	√	√
Motion adaptive de-interlacing	√			√	√	√	√	√
PIP/POP	√			√	√		√	√
TV color system	PAL/SECAM	PAL/SECAM	PAL/NTSC	PAL/SECAM	PAL/NTSC	PAL/NTSC	PAL/SECAM	PAL/NTSC
Program sort	√	√		√			√	
RF Program number	125	200	200	200	200	256	200	200
Signal type detection	√	√		√			√	
OSD Language	15 种	21 种	2 种	21 种	2 种	2 种	21 种	2 种
Audio Power amplifier	10W*2	3W*2	3W*2	7W*2	7W*2	3W*2	10W*2	7W*2
Head Phone out	√						√	√
Audio Graphic Equalizer		√	√	√	√		√	√
AVC	√	√	√	√	√		√	√
尺寸(mm)	320*151	220*90	220*90			220*120	150*240	150*240
主电源	4A@+12v	4A@+12v	4A@+12v	4A@+12v	4A@+12v	4A@+12v	4A@+12v	4A@+12v
待机电源	0.5A@+5v			<1A@+5v	<1A@+5v		<1A@+5v	<1A@+5v